

BTR 555 SEALANT

PRINCIPAL SERVICES

GENERAL PURPOSE SEALANT FOR ALIPHATIC HYDROCARBON LIQUIDS AND GASES INCLUDING GASOLINE, KEROSENE, FUEL AND LUBRICATING OILS, CRUDE DISTILLATES, SWEET OR SOUR NATURAL AND MANUFACTURED GAS WITH WATER OR ORGANIC CONDENSATES, LPG SYSTEMS, DILUTE ACIDS AND ALKALIES, GLYCOLS, TEXTILE PLANTS, AQUEOUS SOLUTIONS, WATER.

RECOMMENDED TEMPERATURE RANGE

-20° F to 500° F

-29° C to 260° C

UNSUITABLE FOR

AROMATIC SOLVENTS
STRONG CHEMICALS
HOT AIR

CONTAINS

VEGETABLE OIL
TREATED CLAY
POLYAMIDE & EPOXY RESINS
POLYTETRAFLUOROETHYLENE
PERFORMANCE ADDITIVES.

PACKAGING

5 QUART CAN
5 GALLON PAIL
STICK (6 sticks to a box)

COLOR

BROWN



LUBRISERV

TELEFAX: (22) 2773 4906 / 9828 2527
sealants@lubriserv.com.br

ASSISTÊNCIA TÉCNICA PERMANENTE