

## **NORDSTROM 1033 SEALANT**

### **PRINCIPAL SERVICES**

1033 VALVE SEALANT IS AN INORGANICALLY-THICKENED SYNTHETIC ESTER DEVELOPED TO PROVIDE VALVE LUBRICATION AND SEALING FOR A VARIETY OF SERVICES OVER A WIDE TEMPERATURE RANGE AND TO MAXIMIZE LUBRICATION INTERVALS. THIS LOW-SOLIDS, OXIDATION RESISTANT FORMULA MINIMIZES PROBLEMS ASSOCIATED WITH SEALANT HARDENING AND SOLIDS BUILDUP. THIS SEALANT IS RECOMMENDED FOR SERVICES INVOLVING ALIPHATIC HYDROCARBON LIQUIDS AND GASES, GASOLINE, KEROSENE, FUEL OILS, CRUDE DISTILLATES, AVIATION AND JET FUELS, NATURAL GAS, AQUEOUS SOLUTIONS AND DILUTE ACIDS AND ALKALIES.

### **RECOMMENDED TEMPERATURE RANGE**

-20° F to 500° F  
-29° C to 260° C

### **UNSUITABLE FOR**

AROMATIC SOLVENTS  
STRONG CHEMICALS  
HOT AIR

### **CONTAINS**

VEGETABLE OIL  
TREATED CLAY  
POLYAMIDE & EPOXY RESINS  
POLYTETRAFLUOROETHYLENE  
PERFORMANCE ADDITIVES.

### **PACKAGING**

5 QUART CAN  
5 GALLON PAIL  
STICK (6 sticks to a box)

### **COLOR**

GREEN



**LUBRISERV**

TELEFAX: (22) 2773 4906 / 9828 2527  
sealants@lubriserv.com.br

**ASSISTÊNCIA TÉCNICA PERMANENTE**