

**VPX VALVE PURGE**

Valve Purge VPX is a microsilica-thickened mixture of dibasic esteres designed to clean sealant delivery systems within a valve which may be clogged with grit or dirt from the line or from sealant residue. VPX softens this debris and permits it to be dislodged and replaced by fresh sealant. The fluid constituents of VPX can have deleterious effects on parts made of Viton. They can also cause slight swelling of Buna-N, but SBR and EP components should not be affected. Valve Purge should be removed from all pumping equipment in a timely fashion and replaced with a suitable valve sealant in order to minimize the product's effect on elastomeric components.

**INSTRUCTIONS FOR THE USE OF VALVE PURGE VPX**

Valve Purge VPX should be injected liberally into the problem valve using a Handgun or Hypregun. The valve should be operated several times during the application if possible. It would be beneficial if the VPX could remain in the valve for 24 hours or more with periodic valve operation. The injection procedure should then be repeated. An excess of the appropriate sealant for the given application should then be injected into the valve.

If valve operation is improved by this procedure but the valve is still not operating properly, repetition of the procedure may be required.

Under conditions of severe sealant deterioration, Valve Purge VPX may not be capable of dislodging sealant residues and valve disassembly and physical cleaning may be required.

**TYPICAL PHYSICAL PROPERTIES**

Color.....	Blue
Density(g/cm <sup>3</sup> ).....	1.09
Flash Point (COC) °F.....	212
°C.....	100

The information and data presented are based upon information believed to be reliable. However, since we cannot foresee or control the varied conditions under which this product may be used, we cannot guarantee that the same results as those described here will be obtained. Samples are available, and each user should independently determine the suitability of this product for their specific purposes.



**LUBRISERV**

TELEFAX: (22) 2773 4906 // 9828 2527  
 sealants@lubriserv.com.br

**ASSISTÊNCIA TÉCNICA PERMANENTE**